

P/N NAS1351-6LE24P

Military-Fasteners.com

Description

Fastener Length: 1-1/2", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS13516LE24P
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-269-3721
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1351-6LE24P Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum
Fastener Length:	1.460 Inches Minimum And 1.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.312 Inches Minimum And 0.316 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Material:	Plastic Locking Feature
Material:	Steel Fastener
Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-6LE24P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.