

## P/N NAS1351-7-20P

## **Description**

Fastener Length: 1-1/4", Thread: 7/16-20, Head Width: 3/8", Thread Length: 1-1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1351720P

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-051-8608

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-7-20P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.090 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.190 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.642 Inches Minimum And 0.656 Inches Maximum
Head Height:	0.430 Inches Minimum And 0.437 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.438 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-7-20P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-7-20P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.