

## P/N NAS1351-8-56P

## **Description**

Fastener Length: 3-17/32", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-1/2

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1351856P
Minimum Qty (MOQ):	1
NSN:	5305-00-001-4782
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-8-56P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum
Fastener Length:	3.469 Inches Minimum And 3.531 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-8-56P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-8-56P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.