

## P/N NAS1351C00-4

## **Description**

Fastener Length: 17/64", Thread: 0-80, Head Width: 3/64", Thread Length: 17/64", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS16996-3 NAS1351C004

SKU / Model: NAS1351C004

Minimum Qty (MOQ): 25

NSN: 5305-00-357-9765

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1351C00-4 Specifications

Thread Direction: Right-hand  Presend Length: 0.209 Inches Minimum And 0.266 Inches Maximum  Fastener Length: 0.234 Inches Minimum And 0.266 Inches Maximum  Head Style: Flat Chamfer  Head Diameter: 0.091 Inches Minimum And 0.096 Inches Maximum  Head Height: 0.057 Inches Minimum And 0.096 Inches Maximum  Internal Drive Style: Hexagon  Nominal Thread Diameter: 0.060 Inches Minimum And 0.050 Inches Maximum  Internal Drive Style: Hexagon  Nominal Thread Diameter: 0.060 Inches Minimum And 0.051 Inches Maximum  Thread Quantity Per Inch: 80  Minimum Tensile Strength: 80000 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 80.0 Rockwell B Minimum Overall  Material: 80000 Pounds Per Square Inch  Material: 80000 Pounds Per Square Inch  Material Document And Classification: 66 Fed Std All Material Responses Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316  Surface Treatment: 9assivate Overall  Surface Treatment Document And Classification: Q-p-35 Fed Spec Single Treatment Response Overall  Thread Series Designator: Unf  Specification/standard Data: 80000-1-10-1-10-1-10-1-1-10-1-10-1-1-10-1-10-1-1-10-1-1-10-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1		
Thread Length:       0.209 Inches Minimum And 0.266 Inches Maximum         Fastener Length:       0.234 Inches Minimum And 0.266 Inches Maximum         Head Style:       Flat Chamfer         Head Diameter:       0.091 Inches Minimum And 0.096 Inches Maximum         Head Height:       0.057 Inches Minimum And 0.060 Inches Maximum         Internal Drive Style:       Hexagon         Nominal Thread Diameter:       0.060 Inches         Width Across Flats:       0.050 Inches Minimum And 0.051 Inches Maximum         Thread Quantity Per Inch:       80         Minimum Tensile Strength:       80000 Pounds Per Square Inch         Hardness Rating:       80.0 Rockwell B Minimum Overall         Minimum Yield Strength:       30000 Pounds Per Square Inch         Material:       Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall         Material Document And Classification:       66 Fed Std All Material Responses Overall         Surface Treatment:       Passivate Overall         Surface Treatment Document And Classification:       Qq-p-35 Fed Spec Single Treatment Response Overall         Thread Series Designator:       Unf	Thread Class:	3a
Fastener Length:  Head Style:  Flat Chamfer  Head Diameter:  0.091 Inches Minimum And 0.096 Inches Maximum  Head Height:  Internal Drive Style:  Hexagon  Nominal Thread Diameter:  0.060 Inches  Width Across Flats:  0.050 Inches Minimum And 0.051 Inches Maximum  Thread Quantity Per Inch:  80  Minimum Tensile Strength:  80000 Pounds Per Square Inch  Hardness Rating:  80.0 Rockwell B Minimum Overall  Minimum Yield Strength:  30000 Pounds Per Square Inch  Material:  Material Document And Classification:  66 Fed Std All Material Responses Overall  Surface Treatment:  Surface Treatment Document And Classification:  Thread Series Designator:  Unf	Thread Direction:	Right-hand
Head Diameter: 0.091 Inches Minimum And 0.096 Inches Maximum Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.050 Inches Minimum And 0.051 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: 30000 Pounds Per Square Inch Material: 5teel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: 0q-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Thread Length:	0.209 Inches Minimum And 0.266 Inches Maximum
Head Diameter:  Head Height:  0.057 Inches Minimum And 0.060 Inches Maximum  Internal Drive Style:  Hexagon  Nominal Thread Diameter:  0.060 Inches  Width Across Flats:  0.050 Inches Minimum And 0.051 Inches Maximum  Thread Quantity Per Inch:  80  Minimum Tensile Strength:  Bound Pounds Per Square Inch  Hardness Rating:  Minimum Yield Strength:  30000 Pounds Per Square Inch  Material:  Material:  Material:  Material Document And Classification:  66 Fed Std All Material Responses Overall  Surface Treatment:  Passivate Overall  Surface Treatment Document And Classification:  Thread Series Designator:  Unf	Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.050 Inches Minimum And 0.051 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Unf	Head Style:	Flat Chamfer
Internal Drive Style:HexagonNominal Thread Diameter:0.060 InchesWidth Across Flats:0.050 Inches Minimum And 0.051 Inches MaximumThread Quantity Per Inch:80Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316Material Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Nominal Thread Diameter:  0.060 Inches  Width Across Flats: 0.050 Inches Minimum And 0.051 Inches Maximum  Thread Quantity Per Inch: 80  Minimum Tensile Strength: 80.00 Pounds Per Square Inch  Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall  Material Document And Classification: 66 Fed Std All Material Responses Overall  Surface Treatment: Passivate Overall  Surface Treatment Document And Classification: Unf  Unf	Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Width Across Flats:  0.050 Inches Minimum And 0.051 Inches Maximum  Thread Quantity Per Inch:  80 Minimum Tensile Strength:  80000 Pounds Per Square Inch  Hardness Rating:  80.00 Rockwell B Minimum Overall  Minimum Yield Strength:  30000 Pounds Per Square Inch  Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall  Material:  66 Fed Std All Material Responses Overall  Surface Treatment:  9assivate Overall  Surface Treatment Document And Classification:  Classification:  Thread Series Designator:  Unf	Internal Drive Style:	Hexagon
Thread Quantity Per Inch:  Minimum Tensile Strength: Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Nominal Thread Diameter:	0.060 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Width Across Flats:	0.050 Inches Minimum And 0.051 Inches Maximum
Hardness Rating: 80.0 Rockwell B Minimum Overall  Minimum Yield Strength: 30000 Pounds Per Square Inch  Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall  Material Document And Classification: 66 Fed Std All Material Responses Overall  Surface Treatment: Passivate Overall  Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall  Thread Series Designator: Unf	Thread Quantity Per Inch:	80
Minimum Yield Strength:  Material:  Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall  Material Document And Classification:  Surface Treatment:  Surface Treatment Document And Classification:  Surface Treatment Document And Classification:  Thread Series Designator:  Unf	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:  Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall  Material Document And Classification:  Surface Treatment:  Surface Treatment Document And Classification:  Classification:  Thread Series Designator:  Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316  Overall  And Classification:  Passivate Overall  Qq-p-35 Fed Spec Single Treatment Response Overall  Unf	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material:  Material Document And Classification:  66 Fed Std All Material Responses Overall  Surface Treatment:  Passivate Overall  Surface Treatment Document And Classification:  Qq-p-35 Fed Spec Single Treatment Response Overall  Thread Series Designator:  Unf	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment:  Surface Treatment Document And Classification:  Thread Series Designator:  Passivate Overall  Qq-p-35 Fed Spec Single Treatment Response Overall  Unf	Material:	
Surface Treatment Document And Classification:  Thread Series Designator:  Unf  Qq-p-35 Fed Spec Single Treatment Response Overall  Unf	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification:  Qq-p-35 Fed Spec Single Treatment Response Overall  Thread Series Designator:  Unf	Surface Treatment:	Passivate Overall
		Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1351 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C00-4">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C00-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.