



★ FASTENERS

Military-Fasteners.com

P/N NAS1351C00-8

Description

Fastener Length: 1/2", Thread: 0-80, Head Width: 3/64", Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C008
Minimum Qty (MOQ):	25
NSN:	5305-01-302-4841
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1351C00-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.445 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.060 Inches
Width Across Flats:	0.0505 Inches Minimum And 0.0510 Inches Maximum
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall
Material Document And Classification:	Astm A493 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C00-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.