

P/N NAS1351C00-8

Description

Fastener Length: 1/2", Thread: 0-80, Head Width: 3/64", Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C008

Minimum Qty (MOQ): 25

NSN: 5305-01-302-4841

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351C00-8 Specifications

Thread Direction: Right-hand Thread Length: 0.445 Inches Minimum And 0.500 Inches Maximum Fastener Length: 0.470 Inches Minimum And 0.500 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.091 Inches Minimum And 0.096 Inches Maximum Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unrf Specification/standard Data: 80205-nas1351 Professional/industrial Association Standard		
Thread Length: O.445 Inches Minimum And 0.500 Inches Maximum Fastener Length: O.470 Inches Minimum And 0.500 Inches Maximum Head Style: Flat Chamfer Head Diameter: O.091 Inches Minimum And 0.096 Inches Maximum Head Height: O.057 Inches Minimum And 0.096 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.060 Inches Width Across Flats: O.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: Boundary Per Inch:	Thread Class:	3a
Fastener Length: O.470 Inches Minimum And 0.500 Inches Maximum Head Style: Flat Chamfer 0.091 Inches Minimum And 0.096 Inches Maximum Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 55000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unrif	Thread Direction:	Right-hand
Head Style: Head Diameter: O.091 Inches Minimum And 0.096 Inches Maximum Head Height: O.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: O.060 Inches Width Across Flats: O.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: Minimum Tensile Strength: Hax000 Pounds Per Square Inch Hardness Rating: Minimum Yield Strength: Discourse Pour Pounds Per Square Inch Material: Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment Document And Classification: Thread Series Designator: Unrf Vorall Vorall Vo	Thread Length:	0.445 Inches Minimum And 0.500 Inches Maximum
Head Diameter: Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Material: Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unrf	Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Height: 0.057 Inches Minimum And 0.060 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unrf	Head Style:	Flat Chamfer
Internal Drive Style: Hexagon Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Nominal Thread Diameter: 0.060 Inches Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unrf Unrf	Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Width Across Flats: 0.0505 Inches Minimum And 0.0510 Inches Maximum Thread Quantity Per Inch: 80 Minimum Tensile Strength: 180000 Pounds Per Square Inch Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material: Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unrf	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 305 Overall Or Steel Comp 305 Overall Or Steel Comp 306 Overall Or Steel Comp 307 Overall Or Steel Comp 308 Overall Or Steel Co	Nominal Thread Diameter:	0.060 Inches
Minimum Tensile Strength: Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Width Across Flats:	0.0505 Inches Minimum And 0.0510 Inches Maximum
Hardness Rating: 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall Minimum Yield Strength: 155000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 305 Overall Or Steel Comp 306 Overall Or Steel Comp 307 Overall Or Steel Comp 308 Overall	Thread Quantity Per Inch:	80
Minimum Yield Strength:155000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 OverallMaterial Document And Classification:Astm A493 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material: Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 306 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 306 Overall Or Steel Comp 306 Overall Or Steel Comp 307 Overall Or Steel Comp 307 Overall Or Steel Comp 308 Overall Or Steel Comp 306 Overall Or Steel Comp 306 Overall Or Steel Comp 307 Overall Or Steel Comp 308 Overall Or Steel Comp 308 Overall Or Steel Comp 307 Overall Or Steel Comp 308 Overall Or Steel C	Hardness Rating:	39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Astm A493 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Cq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Minimum Yield Strength:	155000 Pounds Per Square Inch
Surface Treatment: Surface Treatment Document And Classification: Classification: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unrf	Material:	
Surface Treatment Document And Classification: Classification: Unrf Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unrf	Material Document And Classification:	Astm A493 Assn Std Single Material Response Overall
Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Surface Treatment:	Cadmium Overall And Chromate Overall
		Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1351 Professional/industrial Association Standard	Thread Series Designator:	Unrf
	Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C00-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.