

**Description**

Fastener Length: 3/16", Thread: 1-72, Head Width: 1/16", Thread Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1351C013         |
| Minimum Qty (MOQ):      | 50                  |
| NSN:                    | 5305-00-435-9131    |
| Schedule B:             | 7318.15.6080        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013680, Alum Screws |



## P/N NAS1351C01-3 Specifications

|                                                       |                                                                                                                                |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                             |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                     |
| <b>Thread Length:</b>                                 | 0.130 Inches Minimum And 0.188 Inches Maximum                                                                                  |
| <b>Fastener Length:</b>                               | 0.158 Inches Minimum And 0.188 Inches Maximum                                                                                  |
| <b>Head Style:</b>                                    | Flat Chamfer                                                                                                                   |
| <b>Head Diameter:</b>                                 | 0.112 Inches Minimum And 0.118 Inches Maximum                                                                                  |
| <b>Head Height:</b>                                   | 0.070 Inches Minimum And 0.073 Inches Maximum                                                                                  |
| <b>Internal Drive Style:</b>                          | Hexagon                                                                                                                        |
| <b>Nominal Thread Diameter:</b>                       | 0.073 Inches                                                                                                                   |
| <b>Width Across Flats:</b>                            | 0.063 Inches Minimum And 0.064 Inches Maximum                                                                                  |
| <b>Thread Quantity Per Inch:</b>                      | 72                                                                                                                             |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch                                                                                                   |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall                                                                                                |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch                                                                                                   |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall                                                                                      |
| <b>Surface Treatment:</b>                             | Passivate Overall                                                                                                              |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall                                                                             |
| <b>Thread Series Designator:</b>                      | Unrf                                                                                                                           |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard                                                                     |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C01-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.