



★ FASTENERS

Military-Fasteners.com

P/N NAS1351C01-3

Description

Fastener Length: 3/16", Thread: 1-72, Head Width: 1/16", Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C013
Minimum Qty (MOQ):	50
NSN:	5305-00-435-9131
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N NAS1351C01-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.130 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.158 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.112 Inches Minimum And 0.118 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.073 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.073 Inches
Width Across Flats:	0.063 Inches Minimum And 0.064 Inches Maximum
Thread Quantity Per Inch:	72
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C01-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.