

**Description**

Fastener Length: 3/16", Thread: 1-72, Head Width: 1/16", Thread Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1351C013
Minimum Qty (MOQ):	50
NSN:	5305-00-435-9131
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



## P/N NAS1351C01-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.130 Inches Minimum And 0.188 Inches Maximum
<b>Fastener Length:</b>	0.158 Inches Minimum And 0.188 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.112 Inches Minimum And 0.118 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.073 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.073 Inches
<b>Width Across Flats:</b>	0.063 Inches Minimum And 0.064 Inches Maximum
<b>Thread Quantity Per Inch:</b>	72
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1351 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C01-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.