

Description

Fastener Length: 17/64", Thread: 3-56, Head Width: 15/32", Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1351C034 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-005-8210 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1351C03-4 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.198 Inches Minimum And 0.266 Inches Maximum |
| Fastener Length: | 0.234 Inches Minimum And 0.266 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.154 Inches Minimum And 0.163 Inches Maximum |
| Head Height: | 0.095 Inches Minimum And 0.099 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.099 Inches |
| Width Across Flats: | 0.078 Inches Minimum And 0.479 Inches Maximum |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1351 Professional/Industrial Association Standard |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C03-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.