

Description

Fastener Length: 17/64", Thread: 3-56, Head Width: 15/32", Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C034
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-005-8210
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1351C03-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.198 Inches Minimum And 0.266 Inches Maximum
Fastener Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.154 Inches Minimum And 0.163 Inches Maximum
Head Height:	0.095 Inches Minimum And 0.099 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.099 Inches
Width Across Flats:	0.078 Inches Minimum And 0.479 Inches Maximum
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C03-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.