

P/N NAS1351C04-4

Description

Fastener Length: 1/4", Thread: 4-48, Head Width: 3/32", Thread Length: 9/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C044

Minimum Qty (MOQ): 50

NSN: 5305-01-509-6214

Schedule B: 7318.15.6080

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1351C04-4 Specifications

Thread Direction: Right-hand Thread Length: 0.240 Inches Minimum And 0.282 Inches Maximum Fastener Length: 0.250 Inches Nominal Head Style: Flat Chamfer Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Material Document And Classification: 66 Assn Std All Material Responses Overall Surface Treatment: Passivate Overall	_, , _,	
Thread Length: Fastener Length: 0.250 Inches Nominal Head Style: Flat Chamfer 1.176 Inches Minimum And 0.183 Inches Maximum Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Thread Class:	3a
Fastener Length: Description: Fastener Length: Description: Flat Chamfer Flat Chamfer Description: Description: Description: Description: Flat Chamfer Description: Descript	Thread Direction:	Right-hand
Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum Head Height: 0.108 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80.00 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Thread Length:	0.240 Inches Minimum And 0.282 Inches Maximum
Head Diameter: 0.176 Inches Minimum And 0.183 Inches Maximum 0.108 Inches Minimum And 0.112 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Material: 66 Assn Std All Material Responses Overall	Fastener Length:	0.250 Inches Nominal
Head Height: Internal Drive Style: Hexagon Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Head Style:	Flat Chamfer
Internal Drive Style: Nominal Thread Diameter: 0.112 Inches Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Width Across Flats: 0.094 Inches Minimum And 0.095 Inches Maximum Thread Quantity Per Inch: 48 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: 80000 Pounds Per Square Inch 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Nominal Thread Diameter:	0.112 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 OverallMaterial Document And Classification:66 Assn Std All Material Responses Overall	Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Hardness Rating: Minimum Yield Strength: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 80.0 Rockwell B Minimum Overall 30000 Pounds Per Square Inch Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall 66 Assn Std All Material Responses Overall	Thread Quantity Per Inch:	48
Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material: Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Overall 66 Assn Std All Material Responses Overall	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material: Overall Material Document And Classification: 66 Assn Std All Material Responses Overall	Minimum Yield Strength:	30000 Pounds Per Square Inch
	Material:	
Surface Treatment: Passivate Overall	Material Document And Classification:	66 Assn Std All Material Responses Overall
	Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall		Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unrf	Thread Series Designator:	Unrf
Specification/standard Data: 80205-nas1351 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C04-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.