

Description

Fastener Length: 1/4", Hole Diameter: 1/32", Thread: 6-40, Head Width: 7/64", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C06H4
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-928-7045
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1351C06H4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.170 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Hole Diameter:	0.033 Inches Minimum And 0.039 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C06H4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.