



★ FASTENERS

Military-Fasteners.com

P/N NAS1351C08-24

Description

Fastener Length: 1-1/2", Thread: 8-36, Head Width: 9/64", Thread Length: 7/8", NAS1351 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C0824
Minimum Qty (MOQ):	10
NSN:	5305-01-606-5204
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1351C08-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	1.460 Inches Minimum And 1.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.1640 Inches
Width Across Flats:	0.141 Inches Nominal
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	1180 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Cap, Socket Head, Undrilled, Plain, Corrosion-resistant Steel, Unrf-3a
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ff-s-86 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams2700, Method 1, Type 6 Or Type 7, Class 1 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C08-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.