

**Description**

Fastener Length: 1-1/2", Thread: 8-36, Head Width: 9/64", Thread Length: 7/8", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1351C0824
Minimum Qty (MOQ):	10
NSN:	5305-01-606-5204
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS1351C08-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Nominal
<b>Fastener Length:</b>	1.460 Inches Minimum And 1.500 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.262 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.159 Inches Minimum And 0.164 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.1640 Inches
<b>Width Across Flats:</b>	0.141 Inches Nominal
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	1180 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Cap, Socket Head, Undrilled, Plain, Corrosion-resistant Steel, Unrf-3a
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ff-s-86 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Ams2700, Method 1, Type 6 Or Type 7, Class 1 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C08-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.