

Description

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 8-36, Head Width: 9/64", Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C08H10P
Minimum Qty (MOQ):	10
NSN:	5305-01-391-0328
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1351C08H10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.569 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	36
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C08H10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.