

P/N NAS1351C08H16

Description

Fastener Length: 63/64", Hole Diameter: 3/64", Thread: 8-36, Head Width: 9/64", Thread Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C08H16

Minimum Qty (MOQ): 5

NSN: 5305-00-044-5888

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351C08H16 Specifications

3a
Right-hand
0.875 Inches Minimum
0.970 Inches Minimum And 1.000 Inches Maximum
Flat Chamfer
0.262 Inches Minimum And 0.270 Inches Maximum
0.159 Inches Minimum And 0.164 Inches Maximum
0.044 Inches Minimum And 0.050 Inches Maximum
Hexagon
0.164 Inches
0.141 Inches Minimum And 0.143 Inches Maximum
6
Drilled
36
80000 Pounds Per Square Inch
80.0 Rockwell B Minimum Overall
30000 Pounds Per Square Inch
Round Internal Hexagon
Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
66 Fed Std All Material Responses Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unrf
80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C08H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.