

Description

Fastener Length: 2-3/8", Thread: 5/8-18, Head Width: 1/2", Thread Length: 2-3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C10LN44
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-366-1142
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N NAS1351C10LN44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.264 Inches Minimum And 2.375 Inches Maximum
Fastener Length:	2.375 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	1.107 Inches Minimum And 1.125 Inches Maximum
Head Height:	0.740 Inches Minimum And 0.750 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.625 Inches
Width Across Flats:	0.500 Inches Minimum And 0.505 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Plastic Polyamide Locking Featuresteel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C10LN44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.