

**Description**

Fastener Length: 2-3/8", Thread: 5/8-18, Head Width: 1/2", Thread Length: 2-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351C10LN44                                      |
| Minimum Qty (MOQ):      | 1 EA  |
| NSN:                    | 5305-01-366-1142                                    |
| Schedule B:             | 7318.15.6080  |
| ECCN:                   | 9A991   |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE  
AVAILABLE

## P/N NAS1351C10LN44 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 2.264 Inches Minimum And 2.375 Inches Maximum  |
| <b>Fastener Length:</b>                      | 2.375 Inches Nominal   |
| <b>Head Style:</b>                           | Flat Chamfer   |
| <b>Head Diameter:</b>                        | 1.107 Inches Minimum And 1.125 Inches Maximum  |
| <b>Head Height:</b>                          | 0.740 Inches Minimum And 0.750 Inches Maximum  |
| <b>Locking Feature:</b>                      | Pellet Threads   |
| <b>Internal Drive Style:</b>                 | Hexagon  |
| <b>Nominal Thread Diameter:</b>              | 0.625 Inches   |
| <b>Width Across Flats:</b>                   | 0.500 Inches Minimum And 0.505 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>             | 18   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                      | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall  |
| <b>Material:</b>                             | Plastic Polyamide Locking Featuresteel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener |
| <b>Material Document And Classification:</b> | Astm A493 Assn Std All Material Responses Fastener   |
| <b>Surface Treatment:</b>                    | Cadmium Fastener And Chromate Fastener   |
| <b>Thread Series Designator:</b>             | Unrf   |
| <b>Specification/standard Data:</b>          | 80205-nas1351 Professional/Industrial Association Standard   |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C10LN44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.