

P/N NAS1351C3-12

Description

length: 3/4", thread: 10-32, socket head, corrosion resistant steel, NAS1351 series screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1351C312 MS16996-12

SKU / Model: NAS1351C312

Minimum Qty (MOQ): 50

NSN: 5305-00-788-5487

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351C3-12 Specifications

3a
Right-hand
0.672 Inches Minimum And 0.766 Inches Maximum
0.734 Inches Minimum And 0.766 Inches Maximum
Flat Chamfer
0.303 Inches Minimum And 0.312 Inches Maximum
0.185 Inches Minimum And 0.190 Inches Maximum
Hexagon
0.190 Inches
0.156 Inches Minimum And 0.159 Inches Maximum
32
80000 Pounds Per Square Inch
80.0 Rockwell B Minimum Overall
30000 Pounds Per Square Inch
Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
66 Fed Std All Material Responses Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unf

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.