

**Description**

Fastener Length: 3/4", Thread: 10-32, Head Width: 5/32", Thread Length: 3/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1351C312P
Minimum Qty (MOQ):	10
NSN:	5305-01-206-7231
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1351C3-12P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.658 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.720 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.303 Inches Minimum And 0.312 Inches Maximum
<b>Head Height:</b>	0.185 Inches Minimum And 0.190 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.156 Inches Minimum And 0.159 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp Xm-7 Overall Or Steel Comp 384 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty1,c12 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1351 Professional/Industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3-12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.