

P/N NAS1351C3-14P

Description

Fastener Length: 7/8", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8", flat head, NAS1351 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C314P

Minimum Qty (MOQ): 5

NSN: 5305-01-136-7146

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351C3-14P Specifications

| 3a |
|--|
| Right-hand |
| 0.783 Inches Minimum And 0.875 Inches Maximum |
| 0.845 Inches Minimum And 0.875 Inches Maximum |
| Flat Chamfer |
| 0.303 Inches Minimum And 0.312 Inches Maximum |
| 0.185 Inches Minimum And 0.190 Inches Maximum |
| Hexagon |
| 0.190 Inches |
| 0.156 Inches Minimum And 0.159 Inches Maximum |
| 32 |
| 80000 Pounds Per Square Inch |
| 80.0 Rockwell B Minimum Overall |
| 30000 Pounds Per Square Inch |
| Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall |
| 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall |
| Cadmium Overall |
| Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Overall |
| Unrf |
| 80205-nas1351 Professional/industrial Association Standard |
| |

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3-14P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.