

**Description**

Fastener Length: 1-1/2", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351C324P                              |
| Minimum Qty (MOQ):      | 25 EA                                     |
| NSN:                    | 5305-01-301-7845                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1351C3-24P Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.875 Inches Minimum   |
| <b>Fastener Length:</b>                               | 1.460 Inches Minimum And 1.500 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.303 Inches Minimum And 0.312 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.185 Inches Minimum And 0.190 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Width Across Flats:</b>                            | 0.1562 Inches Minimum And 0.1587 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall  |
| <b>Minimum Yield Strength:</b>                        | 120000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall |
| <b>Material Document And Classification:</b>          | Astm A493 Assn Std All Material Responses Overall  |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unrf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard   |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3-24P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.