

P/N NAS1351C3H16

Description

Fastener Length: 63/64", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C3H16

Minimum Qty (MOQ): 10

NSN: 5305-00-857-4997

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351C3H16 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum |
| Fastener Length: | 0.970 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.303 Inches Minimum And 0.312 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Hole Diameter: | 0.044 Inches Minimum And 0.050 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.156 Inches Minimum And 0.159 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Hole Configuration Style: | Round Internal Hexagon |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrf |
| Specification/standard Data: | 80205-nas1351 Professional/industrial Association Standard |
| | |

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1351C3H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.