



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1351C3H20**

## Description

Fastener Length: 1-1/4", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351C3H20                              |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-172-8378                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1351C3H20 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.875 Inches Minimum   |
| <b>Fastener Length:</b>                               | 1.210 Inches Minimum And 1.250 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.303 Inches Minimum And 0.312 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.185 Inches Minimum And 0.190 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.044 Inches Minimum And 0.050 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Width Across Flats:</b>                            | 0.156 Inches Minimum And 0.159 Inches Maximum  |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall  |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch   |
| <b>Hole Configuration Style:</b>                      | Round Internal Hexagon   |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall  |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unrf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3H20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.