

Description

Fastener Length: 1/4", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1351C3H5 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-342-2877 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1351C3H5 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.312 Inches Nominal |
| Fastener Length: | 0.312 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.303 Inches Minimum And 0.312 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Criticality Code Justification: | Supp |
| Special Features: | Screw Has Drilled Head |
| Material: | Steel Corrosion Resisting Overall |
| Supplementary Features: | Item Is Not Csi But Has Critical Features Such As Heat Treatment, Surface Finish, Or Material Type And Special Insp. Req.s Such As Magnetic Particle Insp. Or Fluorescent Penetrant Inspection |
| Thread Series Designator: | Unf |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3H5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.