

Description

Fastener Length: 1-1/2", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C3LE24
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-119-3614
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1351C3LE24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum
Fastener Length:	1.460 Inches Minimum And 1.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3LE24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.