

Description

Length: 1/2", Thread: 10-32, Head Width: 5/32", Thread Length: 1/2", NAS1351 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C3LE8
Minimum Qty (MOQ):	10
NSN:	5305-01-082-3310
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1351C3LE8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Plastic Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3LE8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.