

Description

Fastener Length: 7/16", Thread: 10-32, Head Width: 5/32", Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C3LL7
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-013-9594
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1351C3LL7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.408 Inches Minimum And 0.438 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 303 Overall
Material Document And Classification:	Qq-s-763,cl 7,ty A Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3LL7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.