



Military-Fasteners.com

P/N NAS1351C3LL8

Description

Fastener Length: 1/2", Thread: 10-32, Head Width: 5/32", Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351C3LL8                              |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-403-3051                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1351C3LL8 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.500 Inches Minimum  |
| <b>Fastener Length:</b>                               | 0.500 Inches Nominal  |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.303 Inches Minimum And 0.312 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.185 Inches Minimum And 0.190 Inches Maximum   |
| <b>Locking Feature:</b>                               | Strip Threads   |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Width Across Flats:</b>                            | 0.156 Inches Minimum And 0.159 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall   |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Plastic Polyamide Locking Feature   |
| <b>Material:</b>                                      | Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener |
| <b>Material Document And Classification:</b>          | Astm A493 Assn Std All Material Responses Fastener  |
| <b>Surface Treatment:</b>                             | Passivate Fastener  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Fastener   |
| <b>Thread Series Designator:</b>                      | Unf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/Industrial Association Standard  |
| <b>Nondefinitive Spec/std Data:</b>                   | 6 Type  |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C3LL8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.