

## P/N NAS1351C4-12

## **Description**

Fastener Length: 3/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 3/4", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

MS16996-23 NAS1351C412

SKU / Model: NAS1351C412

Minimum Qty (MOQ): 25

NSN: 5305-00-229-8801

Schedule B: 7318.15.6080

ECCN: EAR99









# P/N NAS1351C4-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.649 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.1875 Inches Minimum And 0.1900 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Test Data Document:	81348-ff-s-86c Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	unrf

## **How to Order**

