



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1351C4H12P**

## Description

Fastener Length: 3/4", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 3/4", drilled head, NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS1351C4H12P                 |
| Minimum Qty (MOQ):      | 1                             |
| NSN:                    | 5305-01-334-8553              |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



\* See page 2 for technical characteristics

## P/N NAS1351C4H12P Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.679 Inches Minimum And 0.750 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.750 Inches Nominal   |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.375 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.244 Inches Minimum And 0.250 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.047 Inches Nominal   |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Width Across Flats:</b>                            | 0.188 Inches Minimum And 0.190 Inches Maximum  |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall  |
| <b>Hole Configuration Style:</b>                      | Round Internal Hexagon   |
| <b>iii Part Name Assigned By Controlling Agency:</b>  | Navy Special Project   |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| <b>Material Document And Classification:</b>          | Sae 66 Assn Std All Material Responses Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4H12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.