

# P/N NAS1351C4H28

Military-Fasteners.com

#### Description

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1-"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS1351C4H28                              |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-536-6653                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1351C4H28 Specifications

| Thread Class:  | 3a  |
|--|---|
| Thread Direction:  | Right-hand  |
| Thread Length:   | 1.000 Inches Nominal  |
| Fastener Length:   | 1.710 Inches Minimum And 1.750 Inches Maximum   |
| Head Style:  | Flat Chamfer  |
| Head Diameter:   | 0.365 Inches Minimum And 0.375 Inches Maximum   |
| Head Height:   | 0.244 Inches Minimum And 0.250 Inches Maximum   |
| Hole Diameter:   | 0.047 Inches Nominal  |
| Internal Drive Style:  | Hexagon   |
| Nominal Thread Diameter:   | 0.250 Inches  |
| Width Across Flats:  | 0.188 Inches Minimum And 0.190 Inches Maximum   |
| Hole Quantity:   | 6   |
| Hole Type:   | Drilled   |
| Thread Quantity Per Inch:  | 28  |
| Minimum Tensile Strength:  | 80000 Pounds Per Square Inch  |
| Hardness Rating:   | 80.0 Rockwell B Minimum Overall   |
| Minimum Yield Strength:  | 30000 Pounds Per Square Inch  |
| Hole Configuration Style:  | Round Internal Hexagon  |
| Material:  | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall   |
| Material Document And<br>Classification:   | 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66<br>Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall |
| Surface Treatment:   | Passivate Overall   |
| Surface Treatment Document And<br>Qq-p-35 Fed Spec Single Treatment Response Overall |   |
| Thread Series Designator:  | Unjf  |
| Specification/standard Data:   | 80205-nas1351 Professional/industrial Association Standard  |

### How to Order

Order this socket head screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4H28</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.