

P/N NAS1351C4H6

Military-Fasteners.com

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 3/8", drilled, NAS1351 series screw

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C4H6
Minimum Qty (MOQ):	10
NSN:	5305-00-966-8267
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1351C4H6 Specifications

Pread Length: 0.274 Inches Minimum And 0.375 Inches Maximum Fastener Length: 0.345 Inches Minimum And 0.375 Inches Maximum Head Style: Flat Charmfer Blat Charmfer 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.365 Inches Minimum And 0.375 Inches Maximum Head Height: 0.364 Inches Minimum And 0.350 Inches Maximum Head Height: 0.364 Inches Minimum And 0.250 Inches Maximum Head Height: 0.367 Inches Minimum And 0.250 Inches Maximum Hole Diameter: 0.047 Inches Nominal Nominal Thread Diameter: 0.250 Inches Vidth Across Flats: 0.187 Inches Minimum And 0.190 Inches Maximum Vole Quantity: 6 Hole Type: 0.187 Inches Minimum And 0.190 Inches Maximum Vidth Across Flats: 0.000 Pounds Per Square Inch Minimum Tenslle Strength: 80000 Pounds Per Square Inch Winimum Yield Strength: 0.000 Pounds Per Square Inch Hole Configuration Style: Round Internal Hexagon Waterial: 6000 Pounds Per Square Inch Hole Cong 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp	Thread Class:	3a	
Fastener Length:0.345 Inches Minimum And 0.375 Inches MaximumHead Style:Flat Chamfer0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.365 Inches Minimum And 0.250 Inches MaximumHead Height:0.244 Inches Minimum And 0.250 Inches MaximumHead Height:0.244 Inches MominalMole Diameter:0.407 Inches NominalNominal Thread Diameter:0.250 InchesNominal Thread Diameter:0.250 InchesNote Charge States0.187 Inches Minimum And 0.190 Inches MaximumNet Charge States0.187 Inches Minimum And 0.190 Inches MaximumNote Charge States0.187 Inches Minimum And 0.190 Inches MaximumMinimum Thesile Strength:8000 Pounds Per Square InchMinimum Theile Strength:8000 Pounds Per Square InchMinimum Yield Strength:8000 Pounds Per Square InchMinimum Yield Strength:Seel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 315 Overall Or Steel Comp 316 Overall Charset Alexaponse Overall Or 66 Fed Std 21st Material Re	Thread Direction:	Right-hand	
Head Style:Flat ChamferHead Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.365 Inches Minimum And 0.250 Inches MaximumHead Height:0.444 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.047 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 Inches0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity:1018 Inches Minimum And 0.190 Inches MaximumHole Quantity Per Inch:20.000 Pounds Per Square InchHardness Rating:80.000 Pounds Per Square InchHole Configuration Style:80.000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 200 Voerall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or S	Thread Length:	0.274 Inches Minimum And 0.375 Inches Maximum	
Head Diameter:0.365 Inches Minimum And 0.375 Inches MaximumHead Height:0.244 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.047 Inches NominalHole Diameter:0.407 Inches NominalNominal Thread Diameter:0.250 InchesNominal Thread Diameter:0.250 Inches MaximumOutot Spriger:0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:0Hole Type:0Villed7Horad Quantity Per Inche:880000 Pounds Per Square InchHardness Rating:80.000 Pounds Per Square InchHole Configuration Style:80000 Pounds Per Square InchHole Configuration Style:Round Diese Comp 300 Overall Or Steel Std 51th Material Response Overall Or Astm A493 Assn 51d 61th Material Response Overall Or Steel Std 51th Material Response Overall Or Steel Std 51th Material Response Overall Or Astm A493 Assn 51d 61th Material Response Overall Or Steel Std 51th Material Response Overall Or Steel Std 51th Material Response Overall Or Astm A493 Assn 51d 61th Material Response Overall Or Steel Std 51th Material Response Overall Or Astm A493 Assn 51d 61th Material Response Overall Or Steel Std 51th Material Response Overall Or Astm A493 Assn 51d 61th Material Response Overa	Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum	
Head Height:0.244 Inches Minimum And 0.250 Inches MaximumHole Diameter:0.047 Inches NominalHoreral Drive Style:HexagonNominal Thread Diameter:0.250 InchesNominal Thread Diameter:0.250 InchesVildth Across Flats:0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity:0JoilledDilledThread Quantity Per Inch:2880000 Pounds Per Square InchHardness Rating:80.000 Pounds Per Square InchHole Configuration Style:Roudon Internal HexagonMinimum Yield Strength:30000 Pounds Per Square InchHoteral:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Astm A493 Assn Std 6th Material Response Overall Or 6 Fed Std 2th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or Astm A493 As	Head Style:	Flat Chamfer	
Head0.047 Inches NominalInternal Drive Style:HexagonNominal Thread Diameter:0.250 Inches0.250 Inches0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity:70.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:80.000 Pounds Per Square Inch101 Individual Strength:80.00 Rockwell B Minimum OverallMinimum Theisile Strength:80.00 Rockwell B Minimum OverallMinimum Yield Strength:80.00 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 310 Overall Or Steel Comp 305 Overall Or Steel Comp 310 Overall Or Steel Comp 305 Overall Or Steel Comp 310 Overall Or Steel Comp 310 Overall Or Steel Comp 305 Overall Or Steel Comp 310 Overall Or 66 Fed Std 1st Material Response Overall Or 66 Fed Std 1st	Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum	
Internal Drive Style:HexagonNominal Thread Diamete:0.250 Inches Minimum And 0.190 Inches MaximumNoth Across Flats:0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Type:DilledHole Type:0.000 Pounds Per Square InchMinimum Tensile Strength:80000 Pounds Per Square InchBoond Strength:30000 Pounds Per Square InchHardness Rating:0.000 Pounds Per Square InchMinimum Yield Strength:0.000 Pounds Per Square InchBoond Incenal Hexagon0.000 Pounds Per Square InchMaterial:Seel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 305 Overall Or Astm Ad93 Assm Std 6th Material Response Overall Or 66 Fed Std 1st Material Response Overa	Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum	
Nominal Thread Diameter:0.250 InchesNominal Thread Diameter:0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity:DrilledHole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:80000 Pounds Per Square InchBould Strength:30000 Pounds Per Square InchHardness Rating:80.00 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Astm A493 Assn Std 6th Material Response Overall Or 66 Fed Std 1 Material Response Overall Or 66 Fed Std 2 th Materi	Hole Diameter:	0.047 Inches Nominal	
Width Across Flats:0.187 Inches Minimum And 0.190 Inches MaximumHole Quantity:6Hole Quantity Per Inch:70Bardon State Strength:8000 Pounds Per Square InchMinimum Tensile Strength:8000 Pounds Per Square InchBardones Rating:8000 Pounds Per Square InchHardness Rating:8000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:6000 Pounds Per Square InchBaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Stat Material Response Overall Or 6 Fed Std 2th Mat	Internal Drive Style:	Hexagon	
Hole Quantity:6Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:80000 Pounds Per Square InchBardong Per Square Inch80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 305 Overall Or	Nominal Thread Diameter:	0.250 Inches	
Hole Type:DrilledPrilled28Innimum Tensile Strength:8000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 307 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3td Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 65 Fed Std 5th Material Response Ove	Width Across Flats:	0.187 Inches Minimum And 0.190 Inches Maximum	
Arrow28Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 3rd Material Response OverallSurface Treatment Document And Classification:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Hole Quantity:	6	
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 766 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 65 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 65 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 65 Fed St	Hole Type:	Drilled	
Hardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 66 Fed Std 3rd Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Thread Quantity Per Inch:	28	
Minimum Yield Strength:30000 Pounds Per Square InchHole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response OverallSurface Treatment:Pasivate OverallOq-p-35 Fed Spec Single Treatment Response OverallOverallMateriad Series Designator:Unf	Minimum Tensile Strength:	80000 Pounds Per Square Inch	
Hole Configuration Style:Round Internal HexagonMaterial:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5rd Haterial Response Overall Or 66 Fed Std 5rd Material Response Overall Or 66 Fed Std 5rd Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response OverallUnrfUnrf	Hardness Rating:	80.0 Rockwell B Minimum Overall	
Material:Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallUnrfUnrf	Minimum Yield Strength:	30000 Pounds Per Square Inch	
Material:Comp Xm-7 OverallMaterial Document And Classification:66 Fed Std 1st Material Response Overall Or 6 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 5th Material Response Overall Or 65 Fed Std 5th Material Response Overall Or 65 Fed Std 3rd Material Response OverallSurface Treatment Document And Classification:Oq-p-35 Fed Spec Single Treatment Response OverallFiread Series Designator:Unf	Hole Configuration Style:	Round Internal Hexagon	
Classification:Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallIntered Series Designator:Unf	Material:		
Surface Treatment Document Qq-p-35 Fed Spec Single Treatment Response Overall And Classification: Unrf	Material Document And Classification:		
And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Ihread Series Designator: Unrf	Surface Treatment:	Passivate Overall	
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall	
Nondefinitive Spec/std Data: 6 Type	Thread Series Designator:	Unrf	
	Nondefinitive Spec/std Data:	6 Туре	

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4H6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.