

**Description**

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1/2", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351C4H8                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-566-6413                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1351C4H8 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.500 Inches Nominal                                       |
| <b>Fastener Length:</b>                               | 0.500 Inches Nominal                                       |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.375 Inches Maximum              |
| <b>Head Height:</b>                                   | 0.244 Inches Minimum And 0.250 Inches Maximum              |
| <b>Hole Diameter:</b>                                 | 0.047 Inches Nominal                                       |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Width Across Flats:</b>                            | 0.188 Inches Minimum And 0.190 Inches Maximum              |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch                               |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall                            |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch                               |
| <b>Hole Configuration Style:</b>                      | Round  |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                          |
| <b>Material Document And Classification:</b>          | 66 Fed Std Single Material Response Overall                |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall         |
| <b>Thread Series Designator:</b>                      | Unf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/Industrial Association Standard |
| <b>Nondefinitive Spec/std Data:</b>                   | 6 Type   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4H8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.