

Description

Fastener Length: 7/8", Hole Diameter: 3/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C4HLE14
Minimum Qty (MOQ):	5
NSN:	5305-01-580-0947

NO IMAGE
AVAILABLE

P/N NAS1351C4HLE14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Maximum
Fastener Length:	0.875 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ff-s-86 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4HLE14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.