

**Description**

Fastener Length: 5/8", Thread: 1/4-28, Head Width: 3/16", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1351C4LL10P   |
| Minimum Qty (MOQ): | 10 EA            |
| NSN:               | 5305-01-169-1515 |



## P/N NAS1351C4LL10P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.595 Inches Minimum And 0.625 Inches Maximum                     |
| <b>Fastener Length:</b>                               | 0.595 Inches Minimum And 0.625 Inches Maximum                     |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.375 Inches Maximum                     |
| <b>Head Height:</b>                                   | 0.244 Inches Minimum And 0.250 Inches Maximum                     |
| <b>Locking Feature:</b>                               | Strip Fastener  |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Width Across Flats:</b>                            | 0.188 Inches Minimum And 0.190 Inches Maximum                     |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch                                      |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall                                   |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch                                      |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                                 |
| <b>Material Document And Classification:</b>          | Ff-s-86 Fed Spec Single Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type2,class 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4LL10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.