

Description

Fastener Length: 1-3/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1351C4LL6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-603-5716 |



P/N NAS1351C4LL6 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Nominal |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.365 Inches Minimum And 0.375 Inches Maximum |
| Head Height: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.188 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Chamfer Angle: | 30.0 Degrees Minimum And 45.0 Degrees Maximum |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Nas1351 National Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Ams2700,method 1,type 6 Or 7,class 1 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unrf |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C4LL6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.