

Description

NAS1351C6-16 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1351C616 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-080-0679 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1351C6-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Nominal |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.550 Inches Minimum And 0.562 Inches Maximum |
| Head Height: | 0.368 Inches Minimum And 0.375 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.3750 Inches |
| Width Across Flats: | 0.312 Inches Minimum And 0.316 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 7020 Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ff-s-86 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall Or Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 1 Class 2 Fed Spec 1st Treatment Response Overall Or Ff-s-86 Fed Spec 2nd Treatment Response Overall |
| Thread Series Designator: | Unrf |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C6-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.