

# P/N NAS1351C6-28

### **Description**

Fastener Length: 1-3/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1351C628

Minimum Qty (MOQ): 5

NSN: 5305-00-920-0342

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351C6-28 Specifications

Thread Class: 3a  Thread Direction: Right-hand	
Thread Length: 1.250 Inches Minimum	
Fastener Length: 1.710 Inches Minimum And 1.750 Inches Maximum	
Head Style: Flat Chamfer	
<b>Head Diameter:</b> 0.550 Inches Minimum And 0.562 Inches Maximum	
<b>Head Height:</b> 0.368 Inches Minimum And 0.375 Inches Maximum	
Internal Drive Style: Hexagon	
Nominal Thread Diameter: 0.375 Inches	
Width Across Flats: 0.313 Inches Minimum And 0.316 Inches Maximum	
Thread Quantity Per Inch: 24	
Minimum Tensile Strength: 80000 Pounds Per Square Inch	
Hardness Rating: 80.0 Rockwell B Minimum Overall	
Minimum Yield Strength: 30000 Pounds Per Square Inch	
Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Overall	Steel Comp 316
Material Document And Classification: 66 Fed Std All Material Responses Overall	
Surface Treatment: Passivate Overall	
Surface Treatment Document And Classification:  Qq-p-35 Fed Spec Single Treatment Response Overall	
Thread Series Designator: Unrf	
Specification/standard Data: 80205-nas1351 Professional/industrial Association Standard	

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C6-28">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C6-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.