

P/N NAS1351C8-20

Description

Fastener Length: 1-1/4", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351C820

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-966-7965

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1351C8-20 Specifications

Thread Direction: Right-hand Thread Length: 1.150 Inches Minimum Fastener Length: 1.190 Inches Minimum And 1.250 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.735 Inches Minimum And 0.750 Inches Maximum Head Height: 0.492 Inches Minimum And 0.500 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.500 Inches Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Oqp-35 Fed Spec Single Treatment Response Overall Classification: Unif		
Thread Length: 1.150 Inches Minimum Fastener Length: 1.190 Inches Minimum And 1.250 Inches Maximum Head Style: Flat Chamfer Head Diameter: 0.735 Inches Minimum And 0.750 Inches Maximum Head Height: 0.492 Inches Minimum And 0.500 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.500 Inches Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Thread Class:	3a
Fastener Length: Head Style: Flat Chamfer Head Diameter: 0.735 Inches Minimum And 0.750 Inches Maximum Head Height: 0.492 Inches Minimum And 0.500 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.500 Inches Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Unrf	Thread Direction:	Right-hand
Head Style:Flat ChamferHead Diameter:0.735 Inches Minimum And 0.750 Inches MaximumHead Height:0.492 Inches Minimum And 0.500 Inches MaximumInternal Drive Style:HexagonNominal Thread Diameter:0.500 InchesWidth Across Flats:0.375 Inches Minimum And 0.379 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316Material Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Thread Length:	1.150 Inches Minimum
Head Diameter: 0.735 Inches Minimum And 0.750 Inches Maximum Head Height: 0.492 Inches Minimum And 0.500 Inches Maximum Internal Drive Style: Hexagon Nominal Thread Diameter: 0.500 Inches Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: 30000 Pounds Per Square Inch Material: 5teel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Fastener Length:	1.190 Inches Minimum And 1.250 Inches Maximum
Head Height: Internal Drive Style: Hexagon Nominal Thread Diameter: 0.500 Inches Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: Hardness Rating: 80.00 Pounds Per Square Inch Hardness Rating: 80.00 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Thread Series Designator: Unrf	Head Style:	Flat Chamfer
Internal Drive Style:HexagonNominal Thread Diameter:0.500 InchesWidth Across Flats:0.375 Inches Minimum And 0.379 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316Material Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Nominal Thread Diameter: Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 300 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Surface Treatment Document And Classification: Classification: Thread Series Designator: Unrf	Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Width Across Flats: 0.375 Inches Minimum And 0.379 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 80000 Pounds Per Square Inch Hardness Rating: 80.00 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material: Material Document And Classification: 50 Fed Std All Material Responses Overall Surface Treatment: Surface Treatment Document And Classification: Classification: Thread Series Designator: Unrf	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: 80000 Pounds Per Square Inch 80000 Pounds Per Square Inch 80000 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Material: Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Nominal Thread Diameter:	0.500 Inches
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 OverallMaterial Document And Classification:66 Fed Std All Material Responses OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unrf	Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Hardness Rating: 80.0 Rockwell B Minimum Overall Minimum Yield Strength: 30000 Pounds Per Square Inch Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Thread Quantity Per Inch:	20
Minimum Yield Strength: 30000 Pounds Per Square Inch Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Surface Treatment Document And Classification: Classification: Thread Series Designator: Unrf	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material: Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material: Material Document And Classification: 66 Fed Std All Material Responses Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Passivate Overall Qq-p-35 Fed Spec Single Treatment Response Overall Unrf	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Unrf Qq-p-35 Fed Spec Single Treatment Response Overall Unrf	Material Document And Classification:	66 Fed Std All Material Responses Overall
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unrf	Surface Treatment:	Passivate Overall
		Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	Thread Series Designator:	Unrf
Specification/standard Data: 60203-flas1331 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C8-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.