



Military-Fasteners.com

P/N NAS1351C8LN44

Description


Fastener Length: 1-1/4", Thread: 1/2-20, Head Width: 3/8", Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351C8LN44
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-366-1141
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS1351C8LN44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.150 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.250 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.921 Inches Minimum And 0.937 Inches Maximum
Head Height:	0.616 Inches Minimum And 0.625 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Minimum And 0.379 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Plastic Polyamide Locking Featuresteel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351C8LN44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.