



Military-Fasteners.com

P/N NAS1351N08-6

Description

Fastener Length: 3/8", Thread: 8-36, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351N086
Minimum Qty (MOQ):	10
NSN:	5305-01-378-7862
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1351N08-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Width Between Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Internal Drive Style:	Err-090
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.1406 Inches Minimum And 0.1426 Inches Maximum
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N08-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.