

P/N NAS1351N3-20

Description

NAS1351N3-20

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351N320

Minimum Qty (MOQ): 10

NSN: 5305-01-215-5331

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1351N3-20 Specifications

3a
Right-hand
0.875 Inches Minimum
1.210 Inches Minimum And 1.250 Inches Maximum
Flat Chamfer
0.303 Inches Minimum And 0.312 Inches Maximum
0.185 Inches Minimum And 0.190 Inches Maximum
0.044 Inches Minimum And 0.050 Inches Maximum
Hexagon
0.190 Inches
0.1562 Inches Minimum And 0.1587 Inches Maximum
6
Drilled
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum Overall
Round Internal Hexagon
Iron Alloy 660 Overall
Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unrf
80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N3-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.