

Description

Fastener Length: 3/4", Thread: 1/4-28, Head Width: 3/16", Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351N4LL12
Minimum Qty (MOQ):	2
NSN:	5305-01-236-1622
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:

NO IMAGE
AVAILABLE

P/N NAS1351N4LL12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.649 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.1875 Inches Minimum And 0.1900 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N4LL12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.