

## P/N NAS1351N5-12

### **Description**

Fastener Length: 3/4", Thread: 5/16-24, Head Width: 1/4", Thread Length: 3/4",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1351N512

Minimum Qty (MOQ): 10

NSN: 5305-01-378-8611

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351N5-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.306 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.250 Inches Minimum And 0.253 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N5-12">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N5-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.