

**Description**

Length: 2-1/4", Thread: 1/4-24, Head Width: 1/4", Thread Length: 1-1/8", NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1351N536
Minimum Qty (MOQ):	1
NSN:	5305-01-379-9914
Schedule B:	7415.33.8010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1351N5-36 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.125 Inches Minimum
<b>Fastener Length:</b>	2.210 Inches Minimum And 2.250 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.457 Inches Minimum And 0.469 Inches Maximum
<b>Head Height:</b>	0.306 Inches Minimum And 0.312 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.250 Inches Minimum And 0.253 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1531 Professional/Industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N5-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.