

P/N NAS1351N5-40

Description

Fastener Length: 2-1/2", Thread: 1/4-24, Head Width: 1/4", Thread Length: 1-1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351N540

Minimum Qty (MOQ):

NSN: 5305-01-380-0137

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1351N5-40 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Minimum
Fastener Length:	2.460 Inches Minimum And 2.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.250 Inches Minimum And 0.253 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall And Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1531 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N5-40 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.