

Description


Fastener Length: 2-3/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1351N644
Minimum Qty (MOQ):	1
NSN:	5305-01-378-8604
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1351N6-44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum
Fastener Length:	2.690 Inches Minimum And 2.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.3125 Inches Minimum And 0.3160 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1531 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N6-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.