

Description

Fastener Length: 2-63/64", Thread: 3/8-24, Head Width: 5/16", Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1351N648 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-378-8607 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS1351N6-48 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.250 Inches Minimum |
| Fastener Length: | 2.940 Inches Minimum And 3.000 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.550 Inches Minimum And 0.562 Inches Maximum |
| Head Height: | 0.368 Inches Minimum And 0.375 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.3125 Inches Minimum And 0.3160 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall And Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrf |
| Specification/standard Data: | 80205-nas1531 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351N6-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.